

Electric Cable - Sheathed - 3 Cores - H07V-K - 3X1,5mm



Product code:

Reference: CC4315

Technical specifications:

REFERENCE: CC4315
Nominal Voltage: 300/500v
Construction Material: PVC + Kupfer
Certifications: CE - PVC T1 2 -UNE EN 50363-3 -PVC TM2 UNE EN 50363-4-1
Dimensions (mm): 10.000mm
Warranty Years: 10

Product short description:

Unipolar 3 lines of 1.5mm section without sheath with **PVC** insulation built according to the EN-50525-2-31 standard. Installations in ducts located on surfaces or embedded or in similar closed systems. They are also suitable for fixed or protected mounting of luminaires.

It is suitable for protected installations, lighting and command and control switchgear. They are easy to install thanks to their super-slip insulation and great **flexibility**.

Product description:

Electric Cable - 3 Lines - H07V-K - 3X1,5mm

Unipolar 1.5mm cable without sheath with **PVC** insulation built according to the EN-50525-2-31 standard.

Installations in ducts located on surfaces or embedded or in similar closed systems. They are also suitable for fixed or protected mounting of luminaires.

Conductor: **Flexible** polished copper class 5 according to UNE EN 60228. Insulation: PVC type TI 1 according to UNE EN 50363-3.

- Operating voltage: 450 / 750V
- Test voltage: 2,500 V
- Serving temperature: -15 to 70 °C

These cables are easy to install thanks to their super slippery insulation and great flexibility.

Additional images:



Technical Datasheet

