

LED Streetlight Palace Aluminium 40W-50W-65W-100W



Product code:

Reference: PALACE

Technical specifications:

REFERENCE: PALACIO

Rated Power : 40W-50W-65W-100W

Nominal Voltage: 170V-270V

Colour: 3000K-4000K-5000K

CRI - Chromatic Rendiment Index: Bridgelux: 70 Osram: 80

Construction Material: Aluminium +PMMA

Number & Type of LEDs: 40w: SMD3030 Bridgelux. 50w Magnum: SMD3030

OSRAM. 50w DOB: SMD3030 OSRAM - 50W: SMD5050 BRIDGELUX CHIP

Beam Angle (°): 40w:70°-150° - 50w:136°x78° - 90°x90° 100w:136°x78° - 90°x90°

Luminous diodo LED (Lm/W): 40w:160Lm/W - 50W:180Lm/W - 50W

DOB:180Lm/W - 50W 5050: 220Lm/W 65W:200Lm

Luminous Efficiency (Lm/W): 40w:135Lm/W - 50W: 150Lm/W - 50W DOB:

140Lm/W - 50W 5050: 188Lm/W 65W:160Lm

IP : IP65-Outdoor

Diode Life Expectancy (H): 50.000

Dimensions (mm): 440x440xH770

Power Factor (PF): 0.95

Frequency (Hz): 50/60Hz

Temperature Range (°C): -20°C ~ +55°C

On/Off Cycles: 100.000

Starting Time (s): 0,2s

Impact Protection (IK) : IK10

Driver included: GxTronic - MOSO

Energy Rating (2021-UE-2019/2015): A+

Energy Rating (2023 - UE-2019/2015): C

Warranty Years: 5

Product short description:

Different mounting options are available for our cast **aluminium Palace luminaire**:

- Bridgelux 40W Optical Module + GXTronic Driver
- Bridgelux 40W Optical Module + MOSO Driver Driver 1-10V Programmable
- Optical Module 50W Magnum Bridgelux Chip + GXTronic Driver
- Optical module 50W Magnum Bridgelux Chip + Driver MOSO 1-10V Programmable
- Optical module 50W Magnum DOB Osram Chip
- 65W SMD5050 Hight Lumens Bridgelux optic module + GXTronic Driver
- 65W SMD3030 Hight Lumens Bridgelux + Driver MOSO 1-10V Programmable Optical Module
- 65W-42W Optical LED Module SMD3030 High Lumens Bridgelux + Philips Essential Programable Power Driver.

Manufacturing time is 5 to 7 working days.

Product description:

LED Streetlight Palace Aluminium 40W-50W-65W-100W

This **LED Villa Aluminium streetlight** is ideal for decorating any outdoor space. It has an elegant and classic design and an elegant black finish.

The streetlight can be fitted with different features depending on the LED optical module fitted:

- Bridgelux Chip 40W optical module + GXTronic Driver:

- LED optical block with 40W power and is manufactured with a team of 54 LEDs SMD3030 SMD30 4-core LEDs Bridgelux 2240 DS-C30.
- Aperture Angle (°): 70° - 150°.
- LED Diode Efficacy (Lm/W): 160 Lm/w
- Luminous efficacy (Lm/W): 135Lm/W
- CRI: 70
- High quality GXTronic driver with a life of over 50,000 hours.
- Driver 23-42vDC 1000mA+/-5%.

- Optical Module 50W Magnum Osram Chip + GXTronic Driver

- LED optical block with 50W power and is manufactured with a team of 85 SMD3030 3-core OSRAM SMD3030 LEDs.
- Aperture Angle (°): 136°-78°.
- LED Diode Efficacy (Lm/W): 180 Lm/w
- Luminous efficacy (Lm/W): 150Lm/W.
- CRI: 80

Technical Datasheet

- Driver 23-42vDC 1300mA+5%.

- Optical module 50W Magnum DOB Osram Chip

- LED optical block with a power of 50W and is manufactured with a set of 72 OSRAM OS-CORE Sapphire ODB2235S.A. 3-core SMD3030 SMD30 LEDs.
- Aperture Angle (°): 90°x90°.
- LED Diode Efficacy (Lm/W): 180 Lm/w
- Luminous efficacy (Lm/W): 140Lm/W
- CRI: 80
- Driver: DOB GXTRONIC.

- 65W HIGH LUMINOSITY SMD5050 Bridgelux optical module + Driver PHILIPS

- LED optical block with 50W power and is manufactured with a set of 36 SMD5050 8-core BRIDGELUX SMD5050 LEDs.
- Aperture Angle (°): 90°x90°.
- LED Diode Efficacy (Lm/W): 200 Lm/w
- Luminous efficacy (Lm/W): 160Lm/W.
- CRI: 70
- PHILIPS Driver 1-10v - Dimmable + Programmable (5 settings)

-65W SMD3030 Bridgelux Chip + Philips Essential PROGRAMMABLE Xi EP optical module from 42W to 65W.

- LED optical block with a power of 65W and manufactured with a set of 144 SMD3030 LED diodes with 8 Bridgelux 2240 DS-C30 cores.
- Opening angle (°): 156° x 78°
- LED diode efficiency (Lm/W): 210 Lm/w
- Luminous efficiency (Lm/W): 180Lm/W.
- CRI: 75
- Driver: Philips Xitanium Xi EP - 65W - 1.3-2.0A - WL I112 (which allows power programming in a single range from 42W to 65W.)

- Optical modules 100w (2x50w) Magnum Osram Chip + Driver GXTronic

- Optical LED blocks with 50W power and is manufactured with a team of 85 OSRAM 3-core SMD3030 3-core SMD3030 LEDs.
- Aperture Angle (°): 136°-78°.
- LED Diode Efficacy (Lm/W): 180 Lm/w
- Luminous efficacy (Lm/W): 150Lm/W.
- CRI: 80
- Driver 23-42vDC 1300mA+5%.

- Optical module 100W (2x50W) Magnum DOB Osram Chip

- LED optical blocks with 50W power and is manufactured with a team of 72 OSRAM OS-CORE Sapphire ODB2235S.A. 3-core SMD3030 SMD30 LEDs.
- Aperture Angle (°): 90°x90°.
- LED Diode Efficacy (Lm/W): 180 Lm/w
- Luminous efficacy (Lm/W): 140Lm/W
- CRI: 80
- Driver: DOB GXTRONIC.

The luminaire, made of die-cast aluminium, is designed to last in the most extreme outdoor conditions and is painted in baked polyurethane to maximise its durability.

It is a very energy efficient product as it provides a high light output, offering the possibility of reducing electricity consumption by up to 80% and at the same time it is environmentally friendly as it does not pollute.

Uses of the LED Streetlight Palace Aluminium 40W-50W-65W-100W:

- Parks
- Gardens
- Squares
- Avenues
- Wedding halls
- Villas
- Rural houses
- Industrial warehouses

In FactorLED we ensure that our products have QUALITY guarantee and offer all the necessary elements for DISTRIBUTION, IMPORT or WHOLESALE, including the technical data sheet of each LED product.

Additional images:



Technical Datasheet

