

Wall Light Linear LED - NEW WASHINGTON GRAY - 0.44m - 0.94m - 1.44m - 1.94m - IP54



Product code:

Reference: A-09058-G-230

Technical specifications:

REFERENCE: A-09058-G-230
Rated Power : 14W 0.44m - 28W 0.94m - 42W 1.44m - 56W 1.94m - IP54
Nominal Voltage: 85-265V
Colour: 2700K - 3000K - 4000K - 6000K
CRI - Chromatic Rendiment Index: 80
Construction Material: Aluminium+PC
Luminosity-Lm: 1M:1500x2 Lm/2M: 3000 Lmx2 - Strip LED
Number & Type of LEDs: SMD2835 - 140 LEDs/M PCB12mm
Beam Angle (°): 120°
Luminous diode LED (Lm/W): 160 Lm/w
Luminous Efficiency (Lm/W): 110 Lm/W
Dimmable: TRIAC 40%-100%
Certifications: CE - ROHS
IP : IP54
Diode Life Expectancy (H): 40.000
Dimensions (mm): L: 0.44m - 0.94m - 1.44m - 1.94m
Power Factor (PF): 0,91
Frequency (Hz): 50/60Hz
Temperature Range (°C): -20°C ~ +55°C
On/Off Cycles: 100.000
Starting Time (s): 0,2s
Other Information: RAL 9006
Glare Rating (UGR):
Energy Rating (2021-UE-2019/2015): A+
Energy Rating (2023 - UE-2019/2015): G
Warranty Years: 5

Product short description:

Our **professional linear luminaire - WASHINGTON GRAY** - is designed for 24 hours uninterrupted intensive use. Our **wall light** is handmade in Europe - no returns are accepted as it is a bespoke product. 98% pure aluminium, **IP54** light source provides 2 x 1500 lumens per metre - 140 leds/metre SMD 2835 -. Dimmable by TRIAC. 5 year warranty.

Our diffuser is opal white.

Production time is 5 to 7 working days. (Monday to Friday).

Product description:

Linear LED Wall Light - WASHINGTON GRAY - IP54

Our **linear LED wall lights - WASHINGTON** - is a versatile and timeless range, it can be the protagonist in the interior design of a space or adapt to it. Thanks to the various sizes and colours available, it can provide a wide variety of visual sensations that will define the space from a new perspective.

The linear LED **-WASHINGTON-** draws homogeneous lines of light that adapt to a great variety of spaces with a minimum visual impact, solving both general lighting needs and the illumination of vertical planes.

The design of our **wall light** combines high transmittance diffusers that provide great visual comfort and energy efficiency.

The light source of our **linear LED luminaire** incorporates 2 LED strips of 140 Leds/meter of high luminosity SMD2835 that delivers 1500lm/meter; the LED diodes incorporate double gold wire soldering for longer life and reliability. Very low flicker level.

The 140 0.6W LEDs / meter work only at 0.1W; In other words, they work only at 17% of their nominal capacity, with this we ensure that the LED light source does not heat up at all. Being able to work 24 hours uninterrupted and increasing the useful life up to more than 50,000 hours.

Can also be used in high humidity areas as its **IP54** light source is insulated with high quality silicone (UC Class F1 UL94 and VOC free), which prevents yellowing and cracking over the years.

It is connected directly to **220v**, requiring neither a power supply nor a bridge rectifier.

The consumption of the luminaire is 14W for 44cm; 28W for 94cm; 42W for 144cm; and 56W for 194cm.

Made of high purity (98%) 6063/6060 aluminum with UNE EN 755 and UNE EN 12020-1 heat treatment. The luminaire coating is high resistance and quality and is textured in White, Black, and Grey - Qualicoat -, with a 15-micron thickness for a long service life.

Notice: Product subject to change without prior notice. Ensure to use the most recent technical datasheet.

Technical Datasheet

Our linear LED luminaire - **WASHINGTON** - as it is custom made, offers a choice of warmer, neutral or cooler lighting, and silver, white and black anodised finishes. The luminaire is handmade in Europe to the customer's desired size so this product is non-returnable as it is a made to order product.

Production time is 5 to 7 working days.

Uses of the LED Linear Wall Light - WASHINGTON GRAY - IP54

- Shops
- Exhibitions
- Industries
- Offices
- Homes

In FactorLED we ensure that our products have **QUALITY** guarantee and offer all the necessary elements for **DISTRIBUTION**, **IMPORT** or **WHOLESALE**, including the technical data sheet of each LED product.

Additional images:

