

15W Circular LED Downlight - Adjustable - WHITE - CRI+92 - UGR13



Product code:

Reference: 91807-15WUGR13

Technical specifications:

REFERENCE: 91807-15WUGR13

Rated Power : 15w

Nominal Voltage: 85V-265V

Colour: 3000K - 4000K

CRI - Chromatic Rendiment Index: 92

Construction Material: Alumininum+PC

Luminosity-Lm: 1950 Lm

Number & Type of LEDs: Bridgelux Chip Inside 12C3B

Beam Angle (°): 24°

Luminous diodo LED (Lm/W): 160 Lm/w

Luminous Efficiency (Lm/W): 130 Lm/W

Certifications: CE - ROHS

IP : IP44

Diode Life Expectancy (H): 35.000

Dimensions (mm): Ø80mm

Frequency (Hz): 50/60Hz

Temperature Range (°C): -20°C ~ +55°C

On/Off Cycles: 100.000

Starting Time (s): 0,2s

Cut-out Size (mm): Ø75mm

Glare Rating (UGR): 13

Energy Rating (2021-UE-2019/2015): A+

Energy Rating (2023 - UE-2019/2015): E

Warranty Years: 3

Product short description:

The **CIRCULAR LED Downlight 15W** is made of aluminum +PC, its Bridgelux COB diode is high power and has external driver, with good performance of **130Lm/W**. High color **rendering index +92** - PROFESSIONAL COLOR - to enjoy **light quality** and have **real and professional colors**.

It has a **UGR13** which means that it is a luminaire that does not produce glare, making it perfect for work areas.

Product description:

CIRCULAR LED-Downlight 15W - adressierbar - WEISS - CRI+92 - UGR13

The **Foco Downlight LED CIRCULAR 15W** is a very versatile product, which combines good performance and great energy savings. Its small size makes its design perfect

Our module incorporates an **external Driver** that allows the LED to work at **higher powers**, extends the useful life, and **increases the luminous power** of the LED diode, as the heat generated by the driver does not interfere with the diode, thus increasing the useful life of the whole luminaire.

Its **Bridgelux COB** diode delivers 130 lm/W, which makes it highly efficient and energy-saving. Bridgelux is a recognised brand in the manufacture of high quality COB diodes. Some of the specific advantages of the Bridgelux COB diode are:

1. High energy efficiency: they provide powerful light output with relatively low power consumption.
2. High quality of light: they deliver excellent colour rendering (high CRI) and a constant colour temperature, making objects and spaces look more natural and vivid.
3. Compact design: they have a compact and lightweight design, making them easy to integrate into different luminaires.
4. Greater reliability and durability: they are designed to be long-lasting and reliable.

Our downlight has a **UGR13** level - Low UGR level.

UGR stands for "Unified Glare Ratio" and is used to measure the amount of glare that can be perceived by a person in an illuminated environment. A low UGR indicates that the environment has a lower level of glare and therefore provides a better quality of illumination.

Some advantages of having a low UGR are:

1. Increased visual comfort: By reducing glare, the environment becomes more comfortable for the eyes and reduces eyestrain, which can improve productivity and concentration.
2. Improved performance: A low UGR environment provides better quality of light and can improve visual performance, which is especially important in work and study environments.
3. Improved safety: Low UGR can also improve safety in workspaces by reducing the risk of accidents caused by glare.
4. Aesthetically appealing: Environments with a low UGR can be more aesthetically appealing, as objects and surfaces appear clearer and sharper, creating a more pleasant environment.

Technical Datasheet

In summary, a low UGR provides a number of benefits, such as increased visual comfort, improved performance, enhanced safety and attractive aesthetics, making it an important factor to consider when designing and planning lighting in workspaces, study and other environments.

Its **+92 CRI** allows colours to be perceived with total professionalism and accuracy, which is also perfect for photo studios and commercial premises where professional high performance lighting is required.

The CRI, or "Colour Rendering Index", is a measure of a light source's ability to accurately reproduce the colours of objects compared to a natural light source. A high CRI indicates that the light source can reproduce colours more accurately and in greater detail. Advantages of having a high CRI are:

1. More natural and vivid colours: which improves the appearance and perception of objects and spaces.
2. Improved colour perception accuracy: allows more accurate perception of differences between colours, which can be especially important in applications such as fashion, interior design, art and museum lighting.
3. Improved light quality: improves the quality of light in terms of contrast and clarity, which can make objects and surfaces appear sharper and crisper.
4. Improved visual performance: Improves visual performance in tasks that require good colour perception and detail, such as reading, sewing or precision work.
5. Improved visual comfort: With more natural, vivid colours and better detail perception, visual fatigue is reduced and visual comfort is improved, which can enhance well-being and productivity in work and study environments.

The beam of light is of high quality due to its high **CRI+92**, and its primary **angle of 36°**, which gives us the possibility of highlighting specific elements of a room; at the same time it provides us with significant savings in electricity consumption.

Our **Downlight** is made of aluminium +PC, which is a good conductor of heat, which helps to dissipate the heat generated by the LEDs, which in turn prolongs their useful life.

Uses of the ROUND 15W LED Downlight - Adjustable - WHITE - CRI+92 - UGR13

- Bathrooms
- Wardrobes
- Bedrooms
- Showcases
- Shop windows
- Corridors
- Shops
- Commercial premises
- Work areas

In FactorLED we ensure that our products have **QUALITY** guarantee and offer all the necessary elements for **DISTRIBUTION, IMPORT or WHOLESALE**, including the technical data sheet of each LED product.

Additional images:

