

Circular LED Downlight 30W GXtronic | 3CCT | CRI+92 | IP65 | Cut-out Ø145mm



Product code:

Reference: DNRW30W-CCT-91390

Technical specifications:

REFERENCE: DNRW30W
Rated Power : 30W
Nominal Voltage: 85-265V
Colour: SELECTABLE COLOUR: 3000K-4000K-6000K
CRI - Chromatic Rendiment Index: 92
Construction Material: Aluminium+PC
Luminosity-Lm: 2700Lm
Number & Type of LEDs: COB
Beam Angle (°): 24°
Luminous diodo LED (Lm/W): 120Lm/W
Luminous Efficiency (Lm/W): 90 Lm/W
Certifications: CE, CMIM, RoHS
IP : IP65-Outdoor
Diode Life Expectancy (H): 30.000
Dimensions (mm): Ø 229 mm x H 110 mm
Power Factor (PF): 0.9
Frequency (Hz): 50/60Hz
Temperature Range (°C): -20°C ~ +55°C
On/Off Cycles: 100.000
Starting Time (s): 0,2s
Cut-out Size (mm): Ø 145mm
Driver included: DRIVER NO FLICK
Energy Rating (2021-UE-2019/2015): A+
Warranty Years: 5
Units per masterbox: 20

Product short description:

GXtronic 30W Recessed LED Downlight | Adjustable Power & Color | CRI+92 | IP65

This recessed LED downlight features a power selector on the driver (18W, 22W, 26W, 30W) and 3 color temperatures (3000K, 4000K, 6000K), making it easy to adapt to any space. Its modern aluminum design with interchangeable white trim (round or square) allows for a versatile and elegant installation. With a 24° beam angle, high CRI+92, FP+90, and IP65 protection, it is ideal for indoor and outdoor spaces requiring focused, crisp, and professional lighting.

Product description:

Circular LED Downlight 30W GXtronic | 3CCT | CRI+92 | IP65 | Cut-out Ø145mm

The **GXtronic 30W LED Recessed Downlight** is a professional, versatile lighting solution, designed to deliver performance, efficiency, and aesthetic appeal in both indoor and outdoor spaces. Constructed from **high-quality aluminum** with a sleek white finish, this downlight combines **adjustable wattage**, high color rendering, and **dust and moisture protection**, making it ideal for commercial, residential, and technical applications.

Key features:

- **Adjustable power via GXtronic driver:** 18 W / 22 W / 26 W / 30 W
- **3CCT color temperature selector:** 3000 K / 4000 K / 6000 K
- **High CRI>92**
- **Power factor PF>0.90**
- **24° beam angle**
- **Convertible design:** white outer ring interchangeable (round/square)
- **IP65 rating**

Installation dimensions:

- Cut-out diameter: Ø145 mm
- Easy recessed mounting

Technical Datasheet

Recommended applications:

- Offices & retail
- Hotels & restaurants
- Galleries, studios & showrooms
- Private residences
- Covered outdoor areas

With a modern design, professional functionality, and high luminous performance, the GXtronic 30W is an excellent choice for demanding lighting projects.

At FactorLED we ensure that our products have quality guarantee and offer all the necessary elements for DISTRIBUTION, IMPORT or WHOLESALER, including the technical sheet of each LED product.

Additional images:

